


Passive Wireless Sensing at Microwave Frequencies: Challenges and Approachs

Chair for Electrical Instrumentation

Taimur Aftab, Prof. Dr. Leonhard Reindl


- Zero Power RF chipless sensors

“We enable autonomous devices to perceive the environment.”



Wireless sensing principle

- Interrogation of high-Q resonators.




LC Based Wireless Passive Sensor Systems

- Resonance circuit: capacitive sensor and planar coil;
 $f \sim$ quantity to be measured
- Wireless resonance detection
- Sensor Q factor allows for compensation of temperature cross-sensitivity



Silicon micromachined wireless pressure sensor prototype by Bosch




R. Nopper, R. Niekrawietz, L. Reindl, "Wireless Readout of Passive LC Sensors", IEEE Trans. on Instrumentation and Measurement, Vol 59 (9), pp. 2450-2457, Sep 10, 2010

"Inductively Coupled Passive Sensors for Measurements in Difficultly Accessible Environments", Reinhard Nopper¹, Dr. Remigius Has¹, Prof. Dr. Leonhard Reindl², VDI/VDE congress "Sensoren und Messsysteme", Nuremberg, 19. Mai 2010,


¹: Robert Bosch GmbH, Gerlingen-Schillerhöhe, Germany, 2: Laboratory for Electrical Instrumentation, IMTEK, Albert-Ludwigs-Universität Freiburg, Germany

Wireless Passive Sensor Systems Based on Quartz Crystal Resonators



- An external sensor pulls the Quartz resonant frequency
- Might be combined with the mixing sensor


Wireless Passive Sensor Systems Based on Quartz Crystal Resonators




- An external sensor pulls the Quartz resonant frequency
- Might be combined with the mixing sensor



Wireless Passive Sensor Systems Based on High-Q Dielectric Resonators







- Wireless read-out of passive resonators works also for high Q dielectric microwave resonator
- Temperature of operation $> 750^{\circ}\text{C}$




Parallel plate dielectric resonators

- Very high Q resonator
- Used traditionally to characterize DR
- Adjustable resonance frequency
- Operating in the fundamental $TE_{01\delta}$ mode




Wireless Dielectric Temperature Sensor


- Metallization free dielectric resonator based high temperature sensing



Inner view of the oven at 700 °C with a dielectric resonator placed inside





Tracked resonance frequency shift
Maximum frequency shift of -4500 ppm




Complete measurement setup
Reading distance: 1.20 m

Wireless experimental setup

■ Wireless measurement of displacement.





- Range: 1.5 m
- Resolution: $50 \text{ } \sigma/\mu\text{m}$
- Rate: 10 Hz
- Sensitivity: 1ppm/ppm




Force Sensor

- Evanescent open ended waveguide antenna.
- Loaded with a dielectric resonator
- Cantilever beam spring.
- Force \rightarrow Displacement \rightarrow Frequency shift




Idea: Torque sensor

- Dielectric resonator as a transducer.





Implementation: Torque sensor

- Clamp on device.
- Low installation time.
- 2.4 GHz ISM band compatible
- Dual sensors on each side for offset compensation
- Offset due to
 - Temperature
 - Sideways force
 - Coupler imperfections



Results: Torque sensor

- Sensitivity comparison
- Higher sensitivity of indirect displacement based measurement.
- Sensitivity in frequency shift rather than small Wheatstone bridge perturbation.
- Sensor resolution: 25x higher



DUT: $3.9 \text{ (kHz/GHz)}/\mu\epsilon$

DMS: $2 \text{ (}\mu\text{V/V)}/\mu\epsilon$

SAWR: $0.6 \text{ (kHz/GHz)}/\mu\epsilon$



Section Editor-in-Chief


Prof. Dr. Leonhard M. Reindl

Section Board Members

Yuh-Shyan Chen
Jaime Lloret Mauri
Gregory O'Hare
Evangelos Kranakis
Kin K. Leung
Peter Scheuermann
Erol Gelenbe
Mohamed F. Younis
Huseyin Arslan
Davide Brunelli

Mario Collotta
Alessandro Bogliolo
Giancarlo Fortino
Paul J.M. Havinga
Yu Hen Hu
Luciano Lavagno
Rongxing Lu
Stefan Poslad
Joel J.P.C. Rodrigues
Lei Shu

Wendong Xiao
Boon-Chong Seet
Athanasios V. Vasilakos
Emanuel Melachrinoudis
Symeon Papavassiliou
Ana M. Bernardos
Paolo Bellavista
Kemal Akkaya
Dimitrios Georgeakopoulos



Journal's Aims and Scope:

Sensors (ISSN 1424-8220) is an open access journal that provides an advanced forum for studies of sensors, the scope includes:

Physical sensors	Chemical sensors
Biosensors	Sensor technology
<i>Sensor networks</i>	Remote sensors
Sensing principles	Applications of sensors

Author Benefits:

1. High visibility, Rapid publication
2. Unlimited and free access for readers
3. No Copyright Constraints
4. Thorough Peer-Review
5. Coverage by SCIE (Clarivate Analytics), MEDLINE (NLM), PubMed (NLM), Scopus (Elsevier)
6. No Space Constraints, No Extra Space or Color Charges

Page views: 8,500,000+
Citations: 23,000+
Published papers: 12,000+

Journal website:
mdpi.com/journal/sensors

Contact us:
sensors@mdpi.com

Follow us on Twitter:
@Sensors_MDPI